

EMC450P**Monofiber**

COMPOSITE INDUSTRY'S BEST BRANDS

Product Code #	EMC450P
Product Name	Chopped Strand Mat
Product Description	E-glass, Powder,450g/m2.

TECHNICAL DATA SHEETS

Item	Unit	Standard
Density	g/sqm	450±25
Binder Content	%	3.5±1
Moisture	%	≤0.2
Fiber Length	mm	50
Roll Width	mm	150 — 2600
Normal Roll Width	mm	1040 / 1250 / 1270
Roll Net Weight	kgs	30 / 35 / 45
Breaking Strength in Vertical	N/150mm (N)	≥130
Breaking Strength in Horizontal	N/150mm (N)	≥130
Solubility in styrene	s	≤40
Appearance	color	White
Application	Compression molding and also can be used in filament winding, hand lay up process and continuous laminating processes. Mainly for FRP Roofing Sheets.	

Product Picture:

**DongYu Fiberglass**

CHANGSHU DONGYU INSULATED COMPOUND MATERIALS CO., LTD.

Add: Fuchunjiang road, Changshu City, Jiangsu, China 215533

Tel: 0086-512-52521366, 52529500. Fax:0086-512-52525973

Web: www.dongyufiberglass.com

Email: sales@dongyufiberglass.com