

<b>Product Code #</b>	EMC300P
<b>Product Name</b>	Chopped Strand Mat
<b>Product Description</b>	E-glass,Powder,300g/m2.

### TECHNICAL DATA SHEETS

Item	Unit	Standard
Density	g/sqm	300±20
Binder Content	%	4.5±1
Moisture	%	≤ 0.2
Fiber Length	mm	50
Roll Width	mm	150__ 2600
Normal Roll Width	mm	1040 / 1250 / 1270
Roll Net Weight	kgs	30 / 35 / 45
Breaking Strength in Vertical	N/150mm (N)	≥ 110
Breaking Strength in Horizontal	N/150mm (N)	≥ 110
Solubility in styrene	s	≤ 40
Appearance	color	White
Application	Compression molding and also can be used in filament winding, hand lay up process and continuous laminatin processes. Mainly for FRP Roofing Sheets.	

Product Picture:

**DongYu Fiberglass**

CHANGSHU DONGYU INSULATED COMPOUND MATERIALS CO., LTD.

Add: Fuchunjiang road, Changshu City, Jiangsu, China 215533

Tel: 0086-512-52521366, 52529500. Fax:0086-512-52525973

Web: [www.dongyufiberglass.com](http://www.dongyufiberglass.com)Email: [sales@dongyufiberglass.com](mailto:sales@dongyufiberglass.com)