

## TECHNICAL DATASHEET

SAP No. 30007135 Article Description B-S-E-931g/m<sup>2</sup>-1270mm

Textile Structure 7000077 SAERTEX®

### ARTICLE CONSTRUCTION (in accordance with EN 13473-1)

Layer	Construction	Areal weight	Tolerance	Material
3	0 °	331 g/m <sup>2</sup>	+/- 5,0 %	E-glass
2	90 °	288 g/m <sup>2</sup>	+/- 5,0 %	E-glass
1	CSM	300 g/m <sup>2</sup>	+/- 10,0 %	E-glass
Stitching		12 g/m <sup>2</sup>	+/- 3 g/m <sup>2</sup>	synthetic

Fiber input can be determined individually

### FURTHER CHARACTERISTICS

Gauge	7,0	Stitching pattern	tricot-warp	Width (nominal)	1270 mm
Stitch length	3,50 mm	Total tolerance	+/- 6,9 %	Total areal weight	931 g/m <sup>2</sup>

- Labelling (Standard)** Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.
- Packaging (Standard)** Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.
- Storage** With original packaging: No moisture recommendation and direct sunlight. To avoid problems with humidity and electrostatic charge, fabrics to be conditioned 24 hours prior to processing, independent of storage conditions.