

TECHNICAL DATASHEET

SAP No. 30007510 Article Description U-E-640g/m²-1260mm

Textile Structure 7004118 SAERTEX®

ARTICLE CONSTRUCTION (in accordance with EN 13473-1)

Layer	Construction	Areal weight	Tolerance	Material
4	0 °	567 g/m ²	+/- 5,0 %	E-glass
3	45 °	13 g/m ²	+/- 5,0 %	E-glass
2	90 °	35 g/m ²	+/- 5,0 %	E-glass
1	-45 °	13 g/m ²	+/- 5,0 %	E-glass
Stitching		12 g/m ²	+/- 3 g/m ²	synthetic

Fiber input can be determined individually

FURTHER CHARACTERISTICS

Gauge	10,0	Stitching pattern	tricot	Width (nominal)	1260 mm
Stitch length	3,00 mm	Total tolerance	+/- 5,4 %	Total areal weight	640 g/m ²

Labelling (Standard) Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.

Packaging (Standard) Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.

Storage With original packaging: No moisture recommendation and direct sunlight. To avoid problems with humidity and electrostatic charge, fabrics to be conditioned 24 hours prior to processing, independent of storage conditions.